

EP209(M) Premium Matte Coated Paper
防水噴墨紙

Product Specification

| | |
|--------------------------|-----------------------------|
| Weight (g/sqm) | 88 ± 4 |
| Thickness (μm) | 112 ± 6 |
| Opacity (%) | 91 ± 3 |
| Stiffness md (mN) | 6 ± 4 |
| Stiffness cd (mN) | 3 ± 2 |
| Smoothness (fs) (sec) | >30 |
| CIE Whiteness (fs) | 156 ± 6 |
| Shade (D65/10°) (fs) L* | 97.0 ± 2 |
| a* | 3.9 ± 1 |
| b* | -15.0 ± 2 |
| Available size | 17" / 24" / 36" / 44" x 45M |

Applications

Designed for all full colour applications and graphics

CAD、Contract proofing

Best for presentations, photorealistic printouts as well as poster-and sign printing in premium-quality

Compatible Printers

■ Waterbase Latex UV Solvent Indigo Dry Toner Thermal Transfer

Condition of usage and storage

Best printing results achieved in a standard climate of 23° C and 50% relative humidity. For problem-free running, always store the product in original packaging and protect it from direct sunlight and moisture. Before using our medium, check its suitability on your printer and for your planned application. We can assume no liability resulting from technical changes in printers and/or inks. Changes in the product design due to technical further developments will not be announced in advance.